

THERE'S A REASON THEY ______ call it "building" _____ A REPUTATION.



Notes

Paslode P
30'
18 16 1







TABLE OF CONTENTS

Tools at a Glance P 4
Cordless Impulse XP Framing NailerP 8
PowerMaster Plus Framing NailerP 10
Compact Framing NailerP 11
PowerMaster Plus 4" Framing NailerP 12
S200-S16 Framing Air StaplerP 14
S200-W16 Insulation Sheathing StaplerP 15
IMLi200 18 Gauge Brad NailerP 16
IMLi250 16 Gauge Finish NailerP 17
16 Gauge Straight Finish Air StaplerP 18
18 Gauge Brad NailerP 20
18 Gauge Brad Nailer/StaplerP 21
18 Gauge Narrow Soffit StaplerP 23
18 Gauge Narrow Crown Finisher StaplerP 24
US-100 Upholstery/Craft StaplerP 25
HP-100 Headless Pin NailerP 26
20 Gauge Hammer StaplerP 27
FloorMaster Plus™P 28
Miscellaneous FastenersP 30





CORDLESS FRAMING

		TOOL	DESCRIPTION	APPLICATIONS
	Pastode	CORDLESS IMPULSE XP 30°FRAMING NAILER Drive 1200 nails per fuel cell Drive 9000 nails per battery charge Proven for over 25 years Durable. Lightweight. Balanced.	Weight: 7.2 lbs Height: 14-1/2" Length: 12" Nail Capacity: 40 Range: 2" — 3-1/4" Shank: .113131	FRAMING, JOISTS, RAFTERS, SOFFITS, STAIRS, SHEATHING, CRATING, FENCES AND DECKS
	1			DESIGNED FOR: FRAMERS & RENOVATORS
,	(see page P 8 for more details)	PART #: 905800		
		F350-S POWER MASTER+™ Durable construction requires less maintenance. Proven performer for tough job site work with less jams or misfires	Weight: 8.4 lbs Height: 13-3/10" Length: 18" Nail Capacity: (2 strips) 84 Range: 2" — 3-1/2" Shank: .113131	FRAMING, JOISTS, RAFTERS, SOFFITS, STAIRS, SHEATHING, CRATING, FENCES AND DECKS
		Powerful. Enduring. Reliable.		DESIGNED FOR: PROFESSIONAL FRAMERS
	(see page P 10 for more details)	PART #: 501000		
		F325R COMPACT FRAMER [™] Lightest-framing nailer ever (Only 5.9 lbs) Smallest Framer Ever (Only 12' long)	Weight: 5.9 lbs Height: 12-9/10" Length: 12-3/10" Range: 2" — 3-1/4" Shank: .113131 Magagine Capacity: 44	FRAMING, JOISTS, RAFTERS, SOFFITS, STAIRS, SHEATHING, CRATING, FENCES AND DECKS
		Compact. Lightweight	magagine capacity. ++	DESIGNED FOR: PROFESSIONAL RENOVATORS
	(see page P 11 for more details)	PART #: 513000		
		PSN100.1 – 4" FRAMING NAILER 30° Designed to drive 4" nails	Weight: 8.9 lbs Height: 14-1/2" Length: 19" Nail Capacity: 84	LSL, LVL, PSL, AND OSB, ENGINEERED LUMER FOR FRAMING
		Powerful to drive into engineered lumber Powerful. Fast. Durable.	Range: 2" – 4" Shank: .113131	DESIGNED FOR: PROFESSIONAL FRAMERS
	(see page P 12 for more details)	PART #: 502900		





PNEUMATIC STRIP FRAMING NAILERS

Tools at a Glance

		TOOL	DESCRIPTION	APPLICATIONS
ERS		S200 S16P – 16GA. FRAMING AIR STAPLER Heavy duty. Lightweight. Versatile	Weight: 4.9 lbs Height: 10-3/4" Length: 12-3/4" Staple Capacity: 150 Range: 3/4" – 2" Staple Type: 1/2" crown GS16	ROOF SHEATHING, PLYWOOD SHEATHING, VINYL SIDING (WITH ATTACHMENT)
STAPI	(see page P 14 for more details)	PART #: 501230		
FRAMING STAPLERS		S200 W16 – 16GA. INSULATION SHEATHING AIR STAPLER Reliable. Durable. Versatile	Weight: 4.9 lbs Height: 10-3/4" Length: 12-3/4" Staple Capacity: 150 Range: 3/4" — 2" Staple Type: 15/16" Crown	HOUSEWRAP, INSULATION, WIRE LATH AND SHEATHING
	(see page P 15 for more details)	PART #: 501265		
RIM NAILERS		IMLi200 – 18GA. BRAD NAILER Drive 1200 nails per fuel cell Drive 12,000 nails per battery charge Proven for over 25 years Durable. Lightweight. Balanced.	Weight: 4.5 lbs Height: 11-1/2" Length: 11" Nail Capacity: 100 Range: 3/4" - 2" Shank: 18 Gauge	CROWN, BASEBOARD MOULDINGS, PANELLING AND CARPENTRY
ΔW	(see page P 16 for more details)	PART #: 903700		
CORDLESS TRI		IMLi250 16GA. STRAIGHT FINISH NAILER Drive 1200 nails per fuel cell Drive 12,000 nails per battery charge Proven for over 25 years Durable. Lightweight. Balanced.	Weight: 4.6 lbs Height: 11-3/4" Length: 10-1/2" Nail Capacity: 100 Range: 1-1/4" — 2-1/2" Shank: 16 ga. Straight	DOOR AND WINDOW TRIM, CASING, CROWN AND BASEBOARD MOULDING
	(see page P 17 for more details)	PART #: 903800		







		TOOL	DESCRIPTION	APPLICATIONS
		T250S F16 – 16GA. FINISH NAILER Adjustable depth of drive Ergonomic design Lightweight	Weight: 3.90 lbs Height: 10" Length: 10-3/4" Nail Capacity: 100 Range: 3/4" – 2-1/2" Nail Type: 16 ga.	WINDOW AND DOOR TRIM/FINISH APPLICATIONS, PANELLING AND CABINETRY
LERS	(see page P 18 for more details)	PART #: 502140		
PNEUMATIC TRIM NAILERS		P18-200 18 GA. BRAD NAILER Lightweight and well balanced No mar tip Easy to access corners	Weight: 2.9 lbs. Height: 9-1/2" Length: 10-1/4" Nail Capacity: 100 Range: 5/8" — 2" Nail Type: 18 ga. — Smooth, Galvanized	WINDOWS, DOORS, FURNITURE, TRIM APPLICATIONS
EUN	(see page P 20 for more details)	PART #: P18-200	Туре: 18 да.	
PN	(see page P 21 for more details)	P18-FS200 18 GA. BRAD NAILER/STAPLER Lightweight and well balanced No mar tip Easy to access corners PART #: P18-FS200	Weight: 2.9 lbs. Height: 9-1/2" Length: 10-1/4" Nail Capacity: 100 Range: 5/8" — 2" brad nails and 5/8" — 1-1/2" staples (3/16" crown) Type: 18 ga. & 3/16	WINDOWS, DOORS, FURNITURE, TRIM APPLICATIONS
APLERS		N18-125 – 1-1/4" NARROW SOFFIT STAPLER Specifically designed for soffit installation with long narrow nosepiece for tight spots.	Weight: 2.5 lbs. Height: 9" Length: 9-1/4" Staple Capacity: 100 Range: 3/4" — 1 1/4" Staple Type: 3/16" crown GSN18	TRIM/FINISH, PLYWOOD, SOFFITS/FACIAS, UNDERLAYMENT APPLICATIONS
ST	(see page P 23 for more details)	PART #: N18-125		
18 GAUGE STAPL		N18 150 – 1-1/2" NARROW CROWN FINISH STAPLER Heavy Duty for long life 4000 Shots per batt. charge	Weight: 2.8 lbs. Height: 9-3/4" Length: 11-1/2" Staple Capacity: 100 Range: 3/4" — 1 1/2" Staple Type: 3/16" crown GSN18	TRIM/FINISH, PLYWOOD, SOFFITS/FASCIAS, UNDERLAYMENT APPLICATIONS
	(see page P 24 for more details)	PART #: N18-150		



Tools at a Glance

		TOOL		DESCRIPTION	APPLICATIONS
LERS		US-100 — UP CRAFT STAP Easy load maga 5 Staples/secor	LER	Weight: 2.00 lbs. Height: 9-1/2" Length: 12-1/2" Staple Capacity: 100 Range: 3/8" — 9/16" Staple Type: 22 ga. Upholstery	UPHOLSTERY, CRAFTS, LIGHT PANELING AND HOME PROJECT APPLICATIONS
TAP	(see page P 25 for more details)	PART #:	US-100		
LITE GAUGE FASTENING STAPI		23GA HEADL NAILER Lightweight ar No mar tip and	nd compact	Weight: 1.20 lbs. Height: 9-1/4" Length: 7-3/4" Staple Capacity: 100 Range: 1/2" — 1-1/2" Staple Type: 23 ga.	FINE WOODWORKING AND TRIM WORK
סח	(see page P 26 for more details)	PART #:	HP100		
LITE GA		HT550 — 200 HAMMER ST Heavy duty, du clear jam, dura	APLER	Weight: 2.0 lbs Height: 3-1/4" Length: 11-3/4" Staple Capacity: 168 Crown: 1/2" Staple Length: 5/32" – 5/16" Staple Type: 20 ga.	CARPET PADDING, INSULATION, ROOF PAPER, HOUSE WRAP
	(see page P 27 for more details)	PART #:	1013292	1/2" crown	
FLOORING		FLOORMAST 2 IN 1 FLOOF STAPLER Drives staples a meet flooring i fastening speci	RING NAILER/ and cleats to manufacturers	Weight: 10.4 lbs Height: 18" Length: 16" Flooring Fasteners: 15ga staples & 16ga L-cleats Fastener Lengths: 2", 1-3/4, 1-1/2"	3/4" HARDWOOD FLOORING
	(see page P 28 for more details)	PART #:	F2N1-200		







IM325XP Cordless Impulse XP Framing Nailer

Portable freedom on the jobsite without hoses or compressors



INCLUDES

- Cordless Li-ion Framing Nailer, Model IM325XP
- Rechargeable 7.4V Li-ion battery
- Li-ion battery charger
- Rugged carrying case
- Owner's manual
- Safety glasses
- 5/32" Hex Wrench

DESCRIPTION/SUGGESTED SPECIFICATIONS

Cordless Impulse XP Framing Nailer—

IT'S MORE THAN A NAILER, IT'S A NAILING SYSTEM THAT GETS THE JOB DONE RIGHT.

The Paslode Lithium Ion cordless Impulse nailer has provided framers and renovators the ability to wood frame without air hoses for over 25 years. New Li-ion battery technology drives 50% more nails per charge. 2-times faster charge time; 2 minute quick charge drives up to 200 nails. Tool free depth of drive adjustment, non slip grip, dual position utility hook, sequential operation triggers.



ADVANTAGES

- Portable, freedom on the jobsite without hoses or compressors
- Heavy-duty rafter/belt hook for taking jobsite abuse
- Non-slip grip provides comfort and reduces hand fatigue
- Tool free depth-of-drive nail adjustment changes nail depth in an instant – even while wearing gloves
- Nail lockout feature prevents blank driving

- Compact size fits between 16" o.c. studs, joists and roof trusses
- Li-ion battery provides 50% longer run time (up to 9,000 nails per charge) than NiCd battery
- 1-hour Full Charge; 2-minute Quick Charge for Up to 200 shots
- Lightweight 7.2 lbs. including battery for better comfort and control
- Works in cold temperature down to -10°C

SELECTION CHART

Pro-Strip RounDrive Fuel/Nail Packs									
LENGTH	SHANK DIAMETER	SHANK Type	HEAD STYLE	COATING	PRODUCT NUMBER	NAILS PER Pack	FUEL CELLS PER PACK		
2-3/8"	0.113	Smooth	Roundrive	Brite	1238FN	1,000	1		
2-3/8"	0.113	Smooth	Roundrive	Brite	3238FN	3,000	3		
3"	0.120	Smooth	Roundrive	Brite	1300FN	1,000	1		
3"	0.120	Smooth	Roundrive	Brite	3300FN	3,000	3		
3-1/4"	0.120	Smooth	Roundrive	Brite	1325FN	1,000	1		
3-1/4"	0.120	Smooth	Roundrive	Brite	3325FN	3,000	3		

See Page P 13 for additional framing nails that work with this tool.

Paslode®

Cordless Impulse XP Framing Nailer

APPLICATIONS



Framing
Joists and rafters
Soffits
Stairs
Sheathing
Crating
Fences and decks

TOOL ACCESSORIES



Part No. 902513 All Season Orange Fuel Cell

Part No. 901252

Cordless No mar tip



Part No. 902654C Li Ion Battery

Part No. 401482

Impulse Oil



Part No. 902667C Lithium Battery Charger



Part No. 219086 Degreaser





Part No. INSULPROBE Insul2Wood – Insulprobe



Part No. IFW-314 & IWF-238 Nail and Washer Combo - 3-1/4" & 2-3/8" with Galvanized Washers (1000/box)



Rigid installation



Applications Semi-rigid Insulation



House wrap Fastening

SPECIFICATIONS

Part No. 905800 Weight: 7.2 lbs Height: 14-1/2" Length: 12" Width: 4" Speed: 2-3 nails per second Nail Capacity: 40 Range: 2" – 3-1/4" Shank: .113 – .131 Nail Angle: 30° Fuel Type: Spare Framing Fuel Nails per Fuel Cell: Approximately 1200 Fuel life: 21 months from date of manufacture Battery Life: 9000 nails per charge Warranty: 1-year full warranty, 5-year limited warranty

TW Construction Products





PF-350S PowerMaster Plus Framing Nailer

> Durability, Balance and Versatility for all jobs



FRAMING NAILS SELECTION CHART

INCLUDES

PowerMaster™ Plus Pneumatic Framing Nailer Bump fire trigger Hex wrench (on tool) Safety glasses Owner's manual

TOOL ACCESSORIES



Part No. 219090 Pneumatic Oil w/ Antifreeze

asinde

DESCRIPTION/SUGGESTED SPECIFICATIONS

PowerMaster Plus Framing Nailer—

DESIGNED FOR PROFESSIONAL FRAMERS

Heavy-duty jobs require a heavy-duty nailer. That's why the pros turn to the proven performance, durability and driving power, only a Paslode pneumatic framing nailer can provide. When used with Paslode nails, this nailing system can help you drive jobs home on time, every time.



ADVANTAGES

- Frame full walls faster. Heavy duty power.
- Reliable performance that saves time with less maintenance.
 - Durable construction requires less maintenance.
 - Proven performer for tough job site work with less jams or misfires
 - Compact size fits between 16" o.c. studs, joists and rafters.

APPLICATIONS

Framing
Joists and rafters
Soffits
Stairs

Soft grip handle for comfort

- Bolt-on end plug for easier service
- Depth of drive on the tool rather than the compressor saves time and energy
- Rafter hook, moves out of the way when not in need

Sheathing

Adjustable air deflector cap

Fences and decks

Crating

SPECIFICATIONS

Part No. 501000

Weight: 8.4 lbs Height: 13-3/10" Length: 18" Speed: 12 nails per second*, sequential or selectable operation Op. Pres. p.s.i (bar): 90 – 120 (5.5 - 8.3) Nail Capacity: 2 strips (up to 84) Nail Range: 2" – 3.5" in length, .113" – .131" shank diameters Nail Angle: 30° Nail Type: Paslode RounDrive® Offset Full Head Air Req./100p.s.i. (6.9 bar): .082/cycle Op. Pres. p.s.i (bar): 80 — 120 (5.5 — 8.3) Warranty: 90-day limited on wear parts, 1-year limited on magazine parts, 5-year limited on housing and cap parts



F325R Compact Framing Nailer

Lightest weight framer ever



INCLUDES

Compact 30^o Framing Nailer Safety glasses Owner's manual

TOOL ACCESSORIES





Part No. 403720 Pneumatic Oil

Part No. 219090 Pneumatic Oil w/ Antifreeze

DESCRIPTION/SUGGESTED SPECIFICATIONS

Compact Framing Nailer—

DESIGNED FOR RENOVATORS

With this nailing system, you'll have any interior remodeling job done in no time. Get the access and maneuverability you need in tight spaces with this lightweight yet powerful pneumatic nailing system. When used with Paslode nails, this nailing system can help you drive jobs home on time, every time.



ADVANTAGES

- Remodel interiors easier. Lightest weight framer ever.
- Remodel Interiors Easier
- First pneumatic nailer made especially with remodeler's needs in mind
- Fits easily into the tightest spaces such as between 16" o.c. studs
- Great maneuverability to work comfortably overhead
- Lightest-framing nailer ever made: 5.9 lbs
- Quick 2-step nail strip reload
- Soft grip handle for comfort
- Works in bump mode for speed on jobsite

APPLICATIONS



- in	Framing	Sheathing
1	Joists and rafters	Crating
R	Soffits	Fences and decks
Î,	Stairs	

SPECIFICATIONS

Part No. 513000

Weight: 5.9 Pounds Height: 12-9/10" Width: 4-3/10" Length: 12-3/10" Fastener Range: 2" – 3 1/4" Shank: .113 - .131 Magazine Capacity: 44 Op. Pres. p.s.i (bar): 90 – 120

Paslode





PowerMaster Plus 4" Framing Nailer

Proven durability and reliability



INCLUDES

PowerMaster Plus 4" Framing Nailer Safety glasses Owner's manual

TOOL ACCESSORIES



Part No. 403720 Pneumatic Oil

Part No. 219090 Pneumatic Oil w/ Antifreeze

aslode

DESCRIPTION/SUGGESTED SPECIFICATIONS

PowerMaster Plus 4"—

DESIGNED FOR TIMBER FRAMERS

The F400S is the PowerMaster Plus framing nailer with an extended power and driver blade for 4" applications.



ADVANTAGES

- PowerMaster Plus Design Proven durability and reliability
- Versatile Drives a variety of nails from 1-1/2" to 4" in length.
- Ergonomic Design Centre of gravity is closer to the trigger, providing better balance.
- Durable And Reliable Rugged design will stand up to the demands of the job in any kind of weather.

APPLICATIONS



LSL, LVL, PSL, and OSB	Wall Sheathing
Framing	Floor Decking
Roof	

SPECIFICATIONS

Part No. 502900 Weight: 8.9 lbs Height: 14-1/2" Length: 19" Nail Capacity: 84 Range: 2" – 4" Shank: .113 – .131

Back of to tool to Nosepiece: 14.5"

Magazine Angle: 30° Nail Type: 30° Paper Tape, full head/clipped OP. Pres. p.s.i. (bar): 80 – 120 (5.5 – 8.3) Warranty: 90-day limited on wear parts, 6-month limited on magazine parts, 1-year limited on housing and cap parts.



Call our toll free number 800-387-9692 or visit <u>www.itwconstruction.ca</u> for general information. Visit Paslode's web site <u>www.paslode.ca</u> for the most current product and technical information.

Pneumatic Strip Framing Nailers

SELECTION CHART

LENGTH	SHANK DIAMETER	SHANK TYPE	HEAD STYLE	COATING	PRODUCT NUMBER	NAILS PER PACK	QUANTITY PER MASTER	QUANTITY PER SKID
COATING T	(PE: BRITE						<u> </u>	
2"	0.113	Smooth	Roundrive	Brite	097385	6,500	1	80
2"	0.113	Ring	Roundrive	Brite	650273	5,500	1	80
2-3/8"	0.113	Smooth	Roundrive	Brite	50238	5 Strips	1	-
2-3/8"	0.113	Smooth	Roundrive	Brite	404238	1,000	4	-
2-3/8"	0.113	Smooth	Roundrive	Brite	097394	5,000	1	96
2-3/8"	0.113	Ring	Roundrive	Brite	097397	5,000	1	96
3"	0.120	Smooth	Roundrive	Brite	097971	3,000	1	96
3"	0.120	Ring	Roundrive	Brite	097973	3,000	1	96
3"	0.131	Smooth	Roundrive	Brite	650830	2,500	1	96
3-1/4"	0.120	Smooth	Roundrive	Brite	50314	5 Strips	1	125
3-1/4"	0.120	Smooth	Roundrive	Brite	404314	1,000	4	-
3-1/4"	0.120	Smooth	Roundrive	Brite	404058	3,000	1	96
3-1/4"	0.131	Smooth	Roundrive	Brite	650839	2,500	1	96
3-1/4"	0.131	Ring	Roundrive	Brite	097978	2,500	1	96
3-1/2"	0.120	Smooth	Roundrive	Brite	404855	2,500	1	96
3-1/2"	0.131	Smooth	Roundrive	Brite	097987	2,500	1	96
4"	0.131	Smooth	Roundrive	Brite	2X0788	2,500	1	96
COATING T	PE: HEAT TRE	TED						
2-1/4"	0.113	Smooth	Roundrive	Heat Treated	401548	4,000	1	96
COATING T	(PE: HOT DIPPE	D						
2"	0.113	Ring	Offset Oval	Hot Dipped	484200	1,000	4	-
2"	0.113	Ring	Offset Oval	Hot Dipped	403389	2,500	1	150
2-3/8"	0.113	Ring	Offset Oval	Hot Dipped	404856	2,500	1	150
3"	0.120	Ring	Offset Oval	Hot Dipped	404857	1,500	1	150
3 1/4"	0.120	Ring	Offset Oval	Hot Dipped	50314G	5 Strips	1	-
3-1/4"	0.120	Ring	Offset Oval	Hot Dipped	404858	1,500	1	150





Also works with Cordless Impulse Framing Nailer (see page P 8)

PRO-STRIP ROUNDRIVE NAILS FOR USE WITH



POWERMASTER PLUS



COMPACT FRAMER



POWERMASTER PLUS 4" FRAMER



CORDLESS IMPULSE XP FRAMING NAILER





S200-S16 Framing Air Stapler

Compact and lightweight for increased maneuverability



INCLUDES

S200-S16 Framing Air Stapler Safety glasses Quick clear Owner's manual

TOOL ACCESSORIES





Part No. 403720 Pneumatic Oil

Part No. 219090 Pneumatic Oil w/ Antifreeze

DESCRIPTION/SUGGESTED SPECIFICATIONS

S200-S16 Framing Air Stapler—

WITH THE RIGHT STAPLER AND STAPLES, YOU'LL HAVE THE JOB DONE IN NO TIME.

Paslode staples drive flush into even the hardest woods. And, because Paslode staples are made for Paslode air staplers, you'll have fewer jams, fewer misfires and faster loading only a Paslode stapling System can deliver.



ADVANTAGES

- Extended bumper life, over 600,000 cycles without failure
- Two finger trigger provides more control
- Quick-clear nose to clear jams quickly
- Versatile, drives 3/4" 2" standard crown staples
- Top load magazine for easy reload and reduced nail waste

SELECTION CHART

16 Gauge Standard Crown Staples

LENGTH	CROWN SIZE	STAPLE POINT	GAUGE	COATING	PRODUCT NUMBER	STAPLES PER PACK
1"	1/2"	Chisel	16	Galvanized	0T5242	16,500
1-1/4"	1/2"	Chisel	16	Galvanized	0T5238	13,500
1-1/2"	1/2"	Chisel	16	Galvanized	0T2695	10,500
1-3/4"	1/2"	Chisel	16	Galvanized	0T2250	9,000
2"	1/2"	Chisel	16	Galvanized	0T2258	7,500

APPLICATIONS



Roof sheathing

Plywood sheathing

Vinyl siding (with attachment)

SPECIFICATIONS

Part No. 501230 Weight: 4.9 lbs Height: 10-3/4" Length: 12-3/4" Staple Capacity: 150 Staple Range: 3/4" – 2" 16 gauge, standard crown (1/2")

Staple Type: 1/2" crown GS16 Galvanized/Brite Air Req./100p.s.i. (6.9 bar): .040/cycle Op. Pres. p.s.i (bar): 80 — 120 (5.5 — 8.3) Warranty: 1-year limited

Call our toll free number 800-387-9692 or visit <u>www.itwconstruction.ca</u> for general information. Visit Paslode's web site <u>www.paslode.ca</u> for the most current product and technical information.

Paslode



S200-W16 Insulation Sheathing Stapler

Staples with ease, comfort and reliability.



DESCRIPTION/SUGGESTED SPECIFICATIONS **S200-W16 Insulation Sheathing Air Stapler**—

RELIABLE. DURABLE. VERSATILE.

Paslode staples drive flush into even the hardest woods. And, because Paslode staples are made for Paslode staplers, you'll have fewer jams, fewer misfires and faster loading only a Paslode Stapling System can deliver.



ADVANTAGES

- Tool-less quick clear nose removes jams easily
- Soft grip handle, for on the job comfort
- Two finger trigger provides more control
- Extended bumper life, over 600,000 cycles without failure
- Versatile Drives 3/4" 2" wide crown (15/16") for a variety of uses
- Top load magazine Reloads easily and reduces nail waste
- Lightweight and well balanced

SELECTION CHART

	16 Gaug	e Wide	Crown St	taples
--	---------	--------	----------	--------

LENGTH	CROWN SIZE	STAPLE POINT	GAUGE	COATING	PRODUCT NUMBER	STAPLES PER PACK
5/8"	15/16"	Chisel	16	Galvanized	0T2851	25,500
3/4"	15/16"	Chisel	16	Galvanized	404068	9,000
7/8"	15/16"	Chisel	16	Galvanized	404069	9,000
1-1/4"	15/16"	Chisel	16	Galvanized	404071	9,000
1-1/2"	15/16"	Chisel	16	Galvanized	0T2855	10,500

INCLUDES

S200-W16 Insulation Sheathing Air Stapler Safety glasses

Owner's manual

TOOL ACCESSORIES



Part No. 403720 Pneumatic Oil

Part No. 219090 Pneumatic Oil w/ Antifreeze

APPLICATIONS

Housewrap

Insulation

Wlire lath

Sheathing

SPECIFICATIONS

Part No. 501265

Weight: 4.9lbs Height: 10-3/4" Length: 12-3/4" Staple Capacity: 150 Staple Type: Galvanized

Staple Range: 3/4"—2" 16 gauge, wide crown (15/16") Air Req./100p.s.i. (6.9 bar): .040/cycle Op. Pres. p.s.i (bar): 80 — 120 (5.5 — 8.3) Warranty: 1-year limited





IMLi200 18 Gauge Brad Nailer

Lightweight and well balanced



TOOL ACCESSORIES

Lithium Ion 7.4v battery
Lithium Ion Battery Charger
3 Pack of No Mar Tips
Degreaser Cleaner
Impulse Oil
Yellow Fuel Cell (4 pk)

INCLUDES

IMLi200 18 Gauge Brad Nailer Safety glasses Quick clear Owner's manual

DESCRIPTION/SUGGESTED SPECIFICATIONS

18 Gauge Brad Nailer—

WE'VE GOT THE FACTS NAILED.

When you need precision in tight spaces, reach for the lightweight Paslode Cordless Finishing Nailing System. It gives great maneuverability to place the nail exactly where you want it wherever you're working: overhead, on ladders or on your knees. Our portable finish nailer, finish nails and fuel cells are designed to work in tandem so you get the job done right, right away



ADVANTAGES

- Li-lon for 50% more shots (12,000) per charge
- Quick charge to 80% in 30 minutes
- New battery standby position conserves charge
- New easier depth of drive thumbwheel
- New reversible belt hook
- 8% lighter 4.5 lbs with battery (compared with Ni-Cad battery)

SELECTION CHART

18 Gaug	18 Gauge Fuel and Finish Nail Packs									
LENGTH	SHANK DIAMETER	SHANK TYPE	GAUGE	COATING	PRODUCT NUMBER	NAILS PER PACK				
1-1/4"	0.048	Chisel	18	Galvanized	FFP-118114	1,000				
1-1/2"	0.048	Chisel	18	Galvanized	FFP-118112	1,000				
2"	0.048	Chisel	18	Galvanized	FFP-118002	1,000				

See Page P 19 for additional finish nails that work with this tool.

APPLICATIONS





Crown and baseboard mouldings Panelling Carpentry

SPECIFICATIONS

Part No. 903700 Weight: 4.5 lbs Height: 11-1/2" Length: 11" Nail Capacity: 100

Nail Range: 3/4" — 2" Nail Type: 18 ga Warranty: 5-year limited





IMLi250 16 Gauge Finish Nailer

Lightweight and well balanced



TOOL ACCESSORIES

Part No. 902654CLithium Ion 7.4v batteryPart No. 902667CLithium Ion Battery ChargerPart No. 2192363 Pack of No Mar TipsPart No. 219086Degreaser CleanerPart No. 401482Impulse OilPart No. 650039Yellow Fuel Cell (4 pk)

INCLUDES

16 Ga Straight Cordless Li-ion Finish Li-ion Battery Charger No-Mar Tips Rugged Carrying Case Owner's Manual & Safety Glasses

DESCRIPTION/SUGGESTED SPECIFICATIONS

16 Gauge Straight Cordless Finish Nailer

GREAT MANEUVERABILITY.

It gives great maneuverability to place the nail exactly where you want it wherever you're working: overhead, on ladders or on your knees. Our portable finish nailer, finish nails and fuel cells are designed to work in tandem so you get the job done right, right away.



ADVANTAGES

- Powerful precision Finish right the first time.
- Li-ion Battery Drives up to 12,000 nails per charge

Lightweight – Only 4.6 pounds for added

- Use Paslode Universal Trim Fuel Drives approx. 1,000 nails
- Battery Standby Position Conserves battery power
- 1 Hour Rapid Charger 80% charge in 20 min

SELECTION CHART

comfort and control

16 Gauge Fuel and Finish Nail Packs

LENGTH	SHANK DIAMETER	SHANK TYPE	GAUGE	COATING	PRODUCT NUMBER	NAILS PER PACK
1 1/2"	0.063	Chisel	16	Galvanized	FFP-116112	1,000
2"	0.063	Chisel	16	Galvanized	FFP-116002	1,000

See Page P 19 for additional finish nails that work with this tool.

APPLICATIONS



Door and window trim

Casing

Crown and baseboard moulding

SPECIFICATIONS

Part No. 903800 Weight: 4.6 lbs Height: 11-3/4" Length: 10-1/2" Nail Capacity: 100 Nail Range: 1-1/4" - 2-1/2"

Nail Type: 16 ga Straight Warranty: 5-year limited

Paslode





T250S F16 16 Gauge Finish Nailer

> Precise placement Lightweight Compact



DESCRIPTION/SUGGESTED SPECIFICATIONS

T250S F16 – 16 Gauge Finish Nailer—

PRECISION AND POWER, LIKE OUR FINISHING NAILER AND NAILS, MAKE A GREAT PAIR.

Our Pneumatic Finishing Nailer is designed to deliver consistent power to drive nails flush, while our finishing nails feature a chisel point design to help prevent wood splitting. When a system works together this perfectly, the results are easy to see.



ADVANTAGES

- Consistent power even in hard to reach spots.
 - Compact, open line of sight drives nails where you want it to even in tight spots
 - Reliable power, delivers consistent drive energy in all types of wood
 - 16 gauge reduces wood splitting and nail visibility
- Tool-free depth of drive nail adjustment

APPLICATIONS

- Powerful performer drives 3/4" 2 -1/2" nails into the hardest woods
- Nail lockout prevents misdrives and surface damage
- Rotating exhaust cap easily moves dust out of the way



Window and door trim/finish applications

Panelling

Cabinetry

INCLUDES

T250S F16 - 16 Gauge Finish Nailer Safety glasses Carrying case Owner's manual

SPECIFICATIONS

Part No. 502140 Weight: 3.9 lbs Height: 10" Length: 10-3/4" Nail Capacity: 100 (2 strips) Nail Range: 3/4" - 2 1/2" Magazine Angle: Straight

Nail Type: 16 gauge Straight -Smooth, Galvanized

Air Req./80 p.s.i: .040/cycle

Warranty: 90-day limited on wear parts, 6-month limited on magazine parts, 1-year limited on housing and cap parts



16 Gauge Straight Finish Nailer

SELEC	TION CH/	ART				
16 Gai	uge Finis	h Nails				
LENGTH	SHANK DIAMETER	SHANK Type	GAUGE	COATING	PRODUCT NUMBER	NAILS PER PACK
1"	0.063	Chisel	16	Galvanized	095203	5,000
1-1/4"	0.063	Chisel	16	Galvanized	095205	5,000
1-1/2"	0.063	Chisel	16	Galvanized	095257	4,000
1-3/4"	0.063	Chisel	16	Galvanized	095435	2,500
2"	0.063	Chisel	16	Galvanized	095436	2,500
2-1/2"	0.063	Chisel	16	Galvanized	090025	2,500
MULTI	0.063	Chisel	16	Galvanized	116000	2,000
1"	0.063	Chisel	16	Galvanized	116001	1,000
1-1/4"	0.063	Chisel	16	Galvanized	116114	1,000
1-1/2"	0.063	Chisel	16	Galvanized	116112	1,000
1-3/4"	0.063	Chisel	16	Galvanized	116134	1,000
	1					

16

16

16

Galvanized

Galvanized

Galvanized



16 GAUGE FINISH NAILS FOR USE WITH

Chisel

Chisel

Chisel

0.063

0.063

0.063

2"

2-1/4"

2-1/2"



T250S F16 - 16 GAUGE FINISH NAILER



116002

400601

116025

1,000

2,500

1,000

IMLi250 - 16 GAUGE FINISH NAILER





Part No. 403720 Pneumatic Oil



Part No. 219090 Pneumatic Oil w/ Antifreeze





TW Construction Products



P18-200 18 Gauge Brad Nailer

Jobsite tough all metal housing and magazine



SEE PAGE P 22 FOR 18 GAUGE NAILS SELECTION CHART

INCLUDES


P18-200 18 Gauge Brad Nailer 3 no mar tips Air fitting Oil Safety glasses Allen wrenches

DESCRIPTION/SUGGESTED SPECIFICATIONS

P18-200 18 Gauge Brad Nailer —

BUILT-IN SIGHT LINE ON HOUSING AND NOSE TO ENSURE ACCURATE NAILING.

Paslode driving power with the features contractors demand: depth of drive guide, dual action trigger, dry fire lockout, magazine gauge, easy jam clearing, no slip rubber handle, extra no mar tips and 360° adjustable exhaust. Actuation tip behind nose piece for clear view of work surface. Built-in sight line on housing and nose to ensure accurate nailing.



ADVANTAGES

- All metal housing & magazine
- Adjustable drive depth
- Bump & sequential fire switch
- Last nail lockout

- Quick-release nose
- 360° adjustabler exhaust
- 5/8" to 2" nails

APPLICATIONS

- Windows
- Doors
- Furniture

Trim applications

SPECIFICATIONS

Part No. P18-200

Weight: 2.9 lbs Height: 9.5" Length: 10.25" Nail Capacity: 100 Nail Range: 5/8" — 2" Magazine Angle: Straight Nail Type: 18 Gauge - Smooth, Galvanized OP. Pres. p.s.i. (bar): 80-120

Warranty: 90-day limited on wear parts, 6-month limited on magazine parts, 1-year limited on housing and cap parts







P18-FS200 18 Gauge Brad Nailer/ Stapler

Paslode driving power with the features contractors demand



SEE PAGE P 22 FOR 22 GAUGE STAPLES SELECTION CHART

DESCRIPTION/SUGGESTED SPECIFICATIONS P18-FS200 18 Gauge Brad Nailer/Stapler —

BUILT-IN SIGHT LINE ON HOUSING AND NOSE TO ENSURE ACCURATE NAILING.

Paslode driving power with the features contractors demand: depth of drive guide, dual action trigger, dry fire lockout, magazine gauge, easy jam clearing, no slip rubber handle, extra no mar tips and 360° adjustable exhaust. Actuation tip behind nose piece for clear view of work surface. Built-in sight line on housing and nose to ensure accurate nailing.



ADVANTAGES

- All metal housing & magazine
- Adjustable drive depth
- Bump & sequential fire switch
- Last nail lockout

- Quick-release nose
- 360° adjustable exhaust
- 5/8" to 2" Nails, 5/8" to 1-1/2" staples

APPLICATIONS

- Windows
- Doors

Furniture

Trim applications

INCLUDES

P18-FS200 18 Gauge Brad Nailer/Stapler 3 no mar tips Air fitting Oil Safety glasses Allen wrenches

SPECIFICATIONS

Part No. P18-FS200 Weight: 2.9 lbs Height: 9.5" Length: 10.25" Nail Capacity: 100 Nail Range: 5/8" – 2" brad nails and 5/8" – 1-1/2" staples (3/16" crown) Magazine Angle: Straight

Nail Type: 18 Gauge - Smooth, Galvanized Nails and 1/4" Crown Staples

OP. Pres. p.s.i. (bar): 80-120

Warranty: 90-day limited on wear parts, 6-month limited on magazine parts, 1-year limited on housing and cap parts.





18 Gauge Brad Nailers/Stapler

18 Gauge Finish Nails LENGTH SHANK SHANK GAUGE **COATING** PRODUCT **NAILS PER** DIAMETER TYPE NUMBER PACK MULTI 0.048 Chisel 18 Galvanized 118000 2,000 1" 0.048 Chisel Galvanized 118001 1,000 18 2" 0.048 Chisel 18 Galvanized 118002 1,000 3/4" 0.048 Chisel 18 Galvanized 118034 1,000 5/8" 0.048 Chisel 18 Galvanized 118058 1,000 1-1/2" 0.048 Chisel 18 Galvanized 118112 1,000 1-1/4" 0.048 Chisel 18 Galvanized 118114 1,000 1-3/4" 0.048 Chisel 18 Galvanized 118134 1,000 1" 0.048 Chisel 18 Galvanized 950001 3,000 2" 0.048 Chisel 18 Galvanized 950002 3,000 3/4" 0.048 Chisel 950034 18 Galvanized 6,000 5/8" 0.048 Chisel 18 Galvanized 950058 6,000 1-1/2" 0.048 Chisel 18 Galvanized 950112 3,000 1-1/4" 0.048 Chisel 18 Galvanized 950114 3,000 1-3/4" 0.048 Chisel 18 Galvanized 950134 3,000 1-3/16" Chisel 18 0.048 Galvanized 951316 3,000





18 GAUGE FINISH NAILS FOR USE WITH



SELECTION CHART

P18-200 -18 GAUGE BRAD NAILER



P18-FS200 – 18 GAUGE BRAD NAILER/STAPLER



IMLI200 – 18 GAUGE FINISH NAILER

TOOL ACCESSORIES



Part No. 403720 Pneumatic Oil

Paslode



Part No. 219090 Pneumatic Oil w/ Antifreeze



N18-125 1-1/4" Narrow Soffit Stapler

Adjustable Exhaust – Maintains a Cleaner Working Environment





INCLUDES

N18-125 — 1-1/4" Narrow Soffit Stapler Safety glasses Carrying case Owner's manual

TOOL ACCESSORIES





Part No. 403720 Pneumatic Oil

Part No. 219090 Pneumatic Oil w/ Antifreeze

DESCRIPTION/SUGGESTED SPECIFICATIONS

N18-125 – 1-1/4" Narrow Soffit Stapler—

POWERFUL – MOTOR DRIVES INTO THE HARDEST OF WOODS.

Precision pneumatic trim tools to do the job right. Whether you're a professional contractor or a "week-end" craftsman, the compact and durable. Lite Line series has the right tool for any trim or hobby application. Featuring the same rugged quality as our other heavy duty professional tools.



ADVANTAGES

- Ergonomically Balanced and Lightweight To reduce arm fatigue.
- Narrow Nose Piece Allows the tool to fit into tight corners.
- Quick Clear Nose Piece- to reduce down time on the job if a jam should occur.
- Magnesium Metal Housing Durable and provides longer tool life.

SELECTION CHART

18 Gauge 1/4" Crown Staples

LENGTH	CROWN SIZE	STAPLE POINT	GAUGE	COATING	PRODUCT NUMBER	STAPLES PER PACK
1/2"	1/4"	Chisel	18	Galvanized	180121	1,000
3/4"	1/4"	Chisel	18	Galvanized	180341	1,000
1"	1/4"	Chisel	18	Galvanized	180011	1,000
1"	1/4"	Chisel	18	Galvanized	140015	5,000
1 1/4"	1/4"	Chisel	18	Galvanized	181141	1,000
1 1/4"	1/4"	Chisel	18	Galvanized	141145	5,000

APPLICATIONS



Trim/Finish

Plywood

Soffits/facias

Underlayment Applications

SPECIFICATIONS

Part No. N18-125 Weight: 2.5 lbs Height: 9" Length: 9-1/4" Nail Capacity: 100 Nail Range: 3/4" - 1-1/4" Nail Type: GSN 18, 3/16 inch Crown OP. Pres. p.s.i. (bar): 80-120 (5.5-8.3)

Warranty: 90-day limited on wear parts, 6-month limited on magazine parts, 1-year limited on housing and cap parts.

Pasinde





1-1/2" Narrow Crown Finish Stapler

> Ergonomically Balanced and Lightweight – To Reduce Arm Fatigue



INCLUDES

N18-150 — 1-1/2" Narrow Crown Finish Stapler Safety glasses Carrying case Owner's manual

TOOL ACCESSORIES





Part No. 403720 Pneumatic Oil

Part No. 219090 Pneumatic Oil w/ Antifreeze

asiode

DESCRIPTION/SUGGESTED SPECIFICATIONS

N18-150 - 1-1/3" Narrow Crown Finish Stapler—

POWERFUL – MOTOR DRIVES INTO THE HARDEST OF WOODS.

Precision pneumatic trim tools to do the job right. Whether you're a professional contractor or a "week-end" craftsman, the compact and durable. Lite Line series has the right tool for any trim or hobby application. Featuring the same rugged quality as our other heavy duty professional tools.



ADVANTAGES

- Adjustable Exhaust Maintains a cleaner working environment.
- Quick Clear Nose Piece to reduce down time on the job if a jam should occur.
- Narrow Nose Piece Allows the tool to fit into tight corners.
- Magnesium Metal Housing Durable and provides longer tool life.

SELECTION CHART

18 Gauge 1/4" Crown Staples

LENGTH	CROWN SIZE	STAPLE POINT	GAUGE	COATING	PRODUCT NUMBER	STAPLES PER PACK
1/2"	1/4"	Chisel	18	Galvanized	180121	1,000
3/4"	1/4"	Chisel	18	Galvanized	180341	1,000
1"	1/4"	Chisel	18	Galvanized	180011	1,000
1"	1/4"	Chisel	18	Galvanized	140015	5,000
1 1/4"	1/4"	Chisel	18	Galvanized	181141	1,000
1 1/4"	1/4"	Chisel	18	Galvanized	141145	5,000
1 1/2"	1/4"	Chisel	18	Galvanized	141125	5,000

APPLICATIONS



Trim/Finish

Plywood

Soffits/facias

Underlayment Applications

SPECIFICATIONS

Part No. N18-150 Weight: 2.8 lbs Height: 9-3/4" Length: 11-1/2" Nail Capacity: 100 Nail Range: 3/4" - 1-1/2" Nail Type: GSN 18, 3/16 inch Crown OP. Pres. p.s.i. (bar): 80-120 (5.5-8.3)

Warranty: 90-day limited on wear parts, 6-month limited on magazine parts, 1-year limited on housing and cap parts.



US-100 Upholstery/ Craft Stapler

Easy-load Magazine





INCLUDES

US100 Upholstery/Craft Stapler

TOOL ACCESSORIES



Part No. 403720

Part No. 219090

Pneumatic Oil

Pneumatic Oil w/ Antifreeze

DESCRIPTION/SUGGESTED SPECIFICATIONS

US-100 Upholstery/Craft Stapler—

LONG NARROW NOSEPIECE FOR TIGHT SPOTS

Lightweight - At only 2 lbs this tool is very easy to handle and decreases operator fatigue. Heavy-duty driver blade.



ADVANTAGES

- Drives 3/8" 9/16" upholstery staples.
- Fast Shoots 5 staples per second

SELECTION CHART

22 Gaug	ge Uphol	stery Ste	aples	

LENGTH	CROWN SIZE	STAPLE POINT	GAUGE	COATING	PRODUCT NUMBER	STAPLES PER PACK
3/8"	3/8"	Chisel	22	Galvanized	422038	4,000

APPLICATIONS



Upholstery

Crafts

Light paneling

Home project applications

SPECIFICATIONS

Part No. US-100 Weight: 2.8 lbs Height: 9-1/2" Length: 12-1/2" Nail Capacity: 100 Nail Range: 3/8" - 9/16" Nail Type: 22 Gauge Upholstery

OP. Pres. p.s.i. (bar): 80-120 (5.5-8.3)

Warranty: 90-day limited on wear parts, 6-month limited on magazine parts, 1-year limited on housing and cap parts.







HP100 Headless Pin Nailer





TOOL ACCESSORIES





Part No. 403720 Pneumatic Oil

Part No. 219090 Pneumatic Oil w/ Antifreeze

DESCRIPTION/SUGGESTED SPECIFICATIONS

HP100 Headless Pin Nailer—

COMPACT – LIGHTWEIGHT.

Multi-directional exhaust port. Pin nails leave a very small hole for easy finishing and painting.



ADVANTAGES

Quick release nose piece

Drives 1/2" to 1-1/2" pin nails

SELECT	SELECTION CHART												
23 Gau	23 Gauge Pin Nails												
LENGTH	SHANK DIAMETER	SHANK TYPE	GAUGE	COATING	PRODUCT NUMBER	NAILS PER PACK							
1"	0.025	Chisel	23	Brite	323001	3,000							
3/4"	0.025	Chisel	23	Brite	323034	3,000							
1-1/2"	0.025	Chisel	23	Brite	323112	3,000							
1-3/8"	0.025	Chisel	23	Brite	323138	3,000							



INCLUDES

HP100 Headless Pin Nailer Safety glasses Tool case Allen wrench and oil

Fine woodworking and trim work

SPECIFICATIONS

Part No. HP100 Weight: 1.2 lbs Height: 9-1/4" Length: 7-3/4" Nail Capacity: 100 Nail Range: 1/2" - 1-1/2" Magazine Angle: Straight

Nail Type: 23 Gauge - Smooth, Galvanized Pin Nails

OP. Pres. p.s.i. (bar): 80-120

Warranty: 90-day limited on wear parts, 6-month limited on magazine parts, 1-year limited on housing and cap parts.





HT550 20 Gauge Hammer Stapler

Quick Clear Jam Clearing

DESCRIPTION/SUGGESTED SPECIFICATIONS

HT550 – 20 Gauge Hammer Stapler—

HEAVY DUTY, DURABLE CONSTRUCTION.

Precision pneumatic trim tools to do the job right. Whether you're a professional contractor or a "week-end" craftsman, the compact and durable. Lite Line series has the right tool for any trim or hobby application. Featuring the same rugged quality as our other heavy duty professional tools.



ADVANTAGES

- Rear Loading Magazine
- Quick Clear Jam Clearing
- Two Strip Capacity



APPLICATIONS



Carpet Padding Insulation

Roof Paper

House Wrap

INCLUDES

HT550 – 20 Gauge Hammer Stapler

SPECIFICATIONS

Part No. 1013292 Weight: 2.0 lbs Height: 3-1/4" Length: 11-3/4" Staple Capacity: 168 Staple Range: 5/32" - 5/16" Magazine Angle: Staight Nail Type: 20Ga, 1/2" Crown OP. Pres. p.s.i. (bar): N/A (Manual Tool)









Floormaster Plus™ 2 in 1 Flooring Nailer/Stapler





INCLUDES

Tool & Mallet Case

DESCRIPTION/SUGGESTED SPECIFICATIONS

2 in 1 Flooring Nailer/Stapler—

THE PROFESSIONAL GRADE 2 IN 1 FLOORING TOOL.

Optimal performance and solid reliability. Easy maintenance and low cost of ownership. Lightweight - 10.4 lbs



ADVANTAGES

- Easy Actuation
 - Only 4 lbs of pressure anywhere on poppet valve
 - Compact all-around striking surface to avoid marking/damaging walls
- Industry-Best Design & Ergonomics
 - Reverse handle with foam grip for reduced fatigue
 - Compact size for nailing boards closer to the end walls

SELECTION CHART

Flooring Staples and Cleats

	Jourpies					
LENGTH	SHANK DIAMETER	SHANK TYPE	GAUGE	COATING	PRODUCT NUMBER	NAILS PER PACK
1 3/4"	Staple	Chisel	15	Brite	151134	1,000
1 3/4"	Staple	Chisel	15	Brite	155134	5,000
2"	Staple	Chisel	15	Brite	151002	1,000
2"	Staple	Chisel	15	Brite	155002	5,000
2"	Cleat	Cleat	16	Brite	100002	1,000

APPLICATIONS



3/4" Hardwood flooring

SPECIFICATIONS

Part No. F2N1-200 Weight: 10.4 lbs Height: 18" Length: 16"



Flooring Fasteners: 15GA staples & 16GA L-cleats Fastener Lengths: 1-3/4", 2" 15GA staples & 2" 16 GA L-cleats







Miscellaneous Fasteners

SELECTION CHART

MISCELLANEOUS FASTENERS

LENGTH	ТҮРЕ	STAPLE POINT	GAUGE	COATING	PRODUCT NUMBER	CLEATS PER PACK
2"	Cleat	Chisel	16	Brite	150018	1,000
15 Degree Co	oil Nails					
LENGTH	SHANK DIAMETER	SHANK	DEGREE	COATING	PRODUCT NUMBER	NAILS PER PACK
1-1/4"	0.080	Spiral	15	Brite	404501	6,300
1-3/4"	0.080	Spiral	15	Brite	404505	6,300
2"	0.099	Spiral	15	Brite	404582	4,500
2-1/4"	0.099	Spiral	15	Brite	404583	4,500
2-1/2"	0.099	Spiral	15	Brite	404584	4,500
3"	0.12	Spiral	15	Brite	404508	4,500
3-1/4"	0.12	Spiral	15	Brite	404510	4,500
5 Degree H	ot Dipped Coil N	lails				
LENGTH	SHANK DIAMETER	SHANK	DEGREE	COATING	PRODUCT NUMBER	NAILS PER PACK
2"	0.099	Spiral	15	Galvanized	097002	2,500
18 Gauge GE	N-ER-X 7/32" Cr	own Staples				
LENGTH	ТҮРЕ	STAPLE POINT	GAUGE	COATING	PRODUCT NUMBER	STAPLES PE PACK
5/8"	7/32"	Chisel	18	Galvanized	732058	5,000
1"	7/32"	Chisel	18	Galvanized	732001	5,000
1-3/8"	7/32"	Chisel	18	Galvanized	732138	5,000
80 Degree P	ositive Placeme	ent Nails				
LENGTH	SHANK DIAMETER	SHANK	DEGREE	COATING	PRODUCT NUMBER	NAILS PER PACK
1-1/2"	0.148	Smooth	30	Galvanized	650014	3,000
1-1/2"	0.148	Smooth	30	Brite	650026	3,000
1-1/2"	0.148	Smooth	30	Brite	650027	2,500
2-1/2"	0.148	Smooth	30	Brite	650646	1,000







Daclado
Pasione
30





TW **Construction Products**

National Headquarters

120 Travail Road Markham, Ontario, L3S 3J1 Tel: 905-471-7403

800-387-9692

Fax: 905-471-7208 800-668-8688

Technical and Customer Service Support

Tel: 800-387-9692

Fax: 800-668-8688

Regional Warehouses

Markham, Ontario

Coquitlam, British Columbia

Calgary, Alberta

Take Advantage of these Contractor Services from ITW Construction Products Canada

From job sites to engineering firms, from Safety Seminars to on-site services, we hope you take advantage of our many contractor services–at no charge! After all, it's one thing to offer the quality products you need to do your job. It's another to provide you with superior service, engineering expertise and total product support.

At ITW Construction Products Canada, we are proud of the partnerships we have built through the years with our distributor network and contractors. Thanks to quality products, innovative services and on-time delivery, we will continue to build new relationships and strengthen existing ones today... and into the next century.

- Factory representatives with years of training and service experience will go out to your job site to provide you with product, service and technical assistance.
- We provide architects and engineers with complete submittal packages which gives them the technical data needed to specify ITW Construction Products Canada products. Contact your ITW Construction Products Canada Distributor or your nearest Customer Service location to request submittal packages.

Technical Application Assistance:

Our staff of application specialists are ready to assist you with any type of application or code approval question during any phase of your project. Call 1-800-387-9692 between 8:00 a.m. and 5:00 p.m. EST, Monday through Friday.

Distributed By

Ramset, T3, T3Cup, Trakfast, GypFast, Mastershot, Triggershot, Hammershot, PowerPoint, TE Pin and Climacoat are trademarks of Illinois Tools Works, Inc.

A7, C6+, Dynabolt, G5, Hammer-Set, LDT, Multi-Set II, Poly Set, Red Head, Redi-Drive, S7, Striker, and Trubolt are trademarks of ITW Red Head and Illinois Tool Works, Inc.

Teks, TruGrip GT, Scots, Maxiseal, Dek-Cap, Tapcon,SG, Tapcon, Maxi-Set Tapcon, Condrive, E-Z Ancor, E-Z Toggle, Twist-N-Lock, E-Z Lite, E-Z Mini, Stud Solver, Hi-Lo, S-12, Backer-On, Rock-On, DecKing, Dec-U-Drive, Dek-Cap, Grid-Mate, Grid-Mate, PB, Climaseal, Spex, Climacoat, UltraShield, Climashield and Building Ideas That Work are trademarks of ITW Buildex and Illinois Tool Works, Inc.

Sammys, Sammy X-Press, Sammy X-Press It, Sammy X-Press Swivel, Sammy X-Press Sidewinder, Tapcon, Sammy Saddle, Speedy Pole Tool, Spot-Rite Level, and Truss-T Hanger are trademarks of ITW Buildex and Illinois Tool Works, Inc.

The term "Paslode" is a trademark and the Paslode logo and all related product and service names, designs and slogans are Paslode trademarks. Paslode, RounDrive, Impulse, Positive Placement are registered trademarks, PowerFramer and quicklode are trademarks of Illinois Tool Works.

R4, RSS, Kameleon, Fin/Trim, RT Composite, Low Profile Cabinet, Pheinox, Top Star, VWS, Caliburn, and The GRK Fasteners Canada Ltd. and all associated designs and logos are trademarks of GRK Fasteners Canada Ltd., used under license.

Hilti is a registered trademark of Hilti, Corp.

DensGlass is a registered trademark of Georgia Pacific Building Products.

Dekstrip, Dektite, Retrofit Dektite, and Dektite are registered trademarks of Deks Industries Pty Ltd.

Phillips Square-driv is a registered trademark of the Phillips Screw Company.

© 2016 Illinois Tool Works, Inc. Form. No. 11/16

The information and recommendations in this document are based on the best information available to us at the time of preparation. We make no other warranty, expressed or implied, as to its correctness or completeness, or as to the results or reliance of this document.